

FOUNDATIONS FLOORING SPECS:

Dimensions:	7" Wide x 48.6" Long x 4.2mm thick overall (3.2mm core plus 1mm pad)
Packaging:	26.02 sf/ctn, 11 pcs/ctn, 60 ctn/plt
Finish:	12mil Wearlayer, Polyurethane Coating, Embossed
Profile:	4-Sided Painted Bevel
Warranty:	25 Yr Residential, 5 Yr Commercial, 5 Yr Multi-Family

HARMONY FLOORING SPECS:

Dimensions:	
<i>Pheasant, Rosefinch, Taunton, Glencoe</i>	5/7/9" Wide x 60" Long x 6.2mm thick overall (5.2mm core plus 1mm cork pad)
<i>Misty Meadow, Beech, Orchard, Nightingale, Chestnut Grove</i>	9" Wide x 60" Long x 6.2mm thick overall (5.2mm core plus 1mm cork pad)
Packaging:	
<i>Pheasant, Rosefinch, Taunton, Glencoe</i>	23.02 sf/ctn, 8 pcs/ctn, 26 ctn/plt
<i>Misty Meadow, Beech, Orchard, Nightingale, Chestnut Grove</i>	18.6 sf/ctn, 5 pcs/ctn, 48 ctn/plt
Finish:	22mil Wearlayer, Polyurethane Coating, Embossed-in-Register
Profile:	4-Sided Painted Bevel
Warranty:	Lifetime Residential, 15 Yr Commercial, 15 Yr Multi-Family

SONATA FLOORING SPECS:

Dimensions:	4.25" Wide x 48.6" Long x 6.2mm thick overall (5.2mm core plus 1mm pad)
Packaging:	20.1 sf/ctn, 14 pcs/ctn, 48 ctn/plt
Finish:	22mil Wearlayer, Polyurethane Coating, Embossed
Profile:	4-Sided Painted Bevel
Warranty:	Lifetime Residential, 15 Yr Commercial, 15 Yr Multi-Family



Mar 2021



AUDACITY SPC

TRIM PROFILES & MEASUREMENTS

TRIM DESCRIPTION

QUARTER ROUND

Applied to cover the expansion gap between the flooring and the wall.

END CAP

Often times called Square Edge or Threshold, used when butting up to carpet or a sliding glass door.

T-MOLD

Joins two floors of equal height, such as in a doorway, between two rooms or in a large area where the maximum length/width is exceeded.






STAIR NOSE

Ends flooring at the top of either a landing or downward staircase.

REDUCER

Ends the flooring onto a surface such as concrete.

TRIM PROFILE



TRIM DIMENSIONS

