


SPC 2.0 MM, 9 MIL

Construction	Luxury Vinyl Tile
Classification	ASTM F1700, Class III, Type B
Dimensions	7" Wide x 48" Long, 177.8 mm x 1219.2 mm
Overall Thickness	2 mm
Wear Layer	9 mil
Finish Coat	Polyurethane with Densified Ceramic Coating
Texture	Embossed
Edge Profile	4-sided Square Edge
Packaging	51.31 sf/carton - 50 cartons/pallet - 2565.5 sf/pallet



Installation & Maintenance

Glue Down Adhesive: Residential & Multi-Family - WF Taylor Dynamic

Commercial - WF Taylor Pinnacle or Resolute

Ambient & Surface Temperature at Installation: 60 - 85 Degrees Fahrenheit

Maintenance: No Polish, Fresh Floors by Taylor

Test Method & Requirements

Solid Vinyl Floor Tile	ASTM F1700	Pass
Flexibility	ASTM F137	Pass
Thickness	ASTM F386	Pass
Wear Layer Thickness	ASTM F410	Pass
Stain/Chemical Resistance	ASTM F925	Pass
Resistance to Heat Color Change	ASTM F1514	Pass
Resistance to Light Color Change	ASTM F1515	Pass
Residual Indentation	ASTM F1914	Pass
Size & Squareness	ASTM F2055	Pass
Dimensional Stability w/Exposure to Heat	ASTM F2199	Pass
Static Coefficient of Friction Polished Surface	ASTM D2047	Exceeds Standard
Static Load Limit	ASTM F970	PASS >250 LBS
Flammability/Radiant Flux	ASTM E648	Class I
Smoke Density	ASTM E662	Pass

Health & Environmental

FloorScore Certified # SCS-FS-05749

Phthalate-Free

Warranty

5 Yr Light Commercial, 5 Yr Multi-Family, 10 Yr Residential

Layout Options:

